

**Inventor:**

**Assignee:**

## General Instrument Corporation



[illegible]

**[0004]** One service that is increasingly available to the users of PSTN is speed-dialing via voice recognition systems and other memory or processor intensive applications for which the centralization of PSTN provides a suitable level of economy. The commercial acceptance of Internet Protocol network telephony can be advanced by systems that offer similar services at a competitive price-point.

**[0005]** The present invention provides architecture and method for providing VoIP customers the ability to use such processor and memory intensive services as the voice recognition dialing of telephone numbers without requiring them to bear the cost of the associated hardware on an individual basis. Instead, these capabilities are localized in a dial server that provides this service for a large number of customers, thereby enabling the cost of the hardware to be distributed over a broad client base at much reduced cost to individual subscribers.

2

Docket: D2647

Telephony Adapter, or MTA), which in turn sends it to a call agent. The call agent uses this number to further route the call to its destination.

#### Brief Description of the Drawings

539  
21

~~[0007]~~ Figure 1 is a block diagram of the logical connections between the elements of this.

[0008] Figure 2 is a sequence diagram of an embodiment of the invention.

#### Detailed Description

[0009] Figure 1 schematically illustrates the invention. Figure 2 provides the corresponding sequence diagram. The system utilizes a Call Agent (CA) and a local gateway, herein referred to as a Media Telephony Adapter (MTA). Generally speaking, the Call Agent handles the basic technical aspects of forming a connection. For example, the CA handles call control operations, and has access to data bases that define the location, type, and internet addresses of the end points. The MTA serves as a local gateway, and packetizes the voice traffic into data frames (also known as IP datagrams or datapackets) for transmission over IP network, and thence to a second gateway or telco for reassembly for the benefit of users at the far end of the connection (where both ends utilize VoIP). The MTA also translates incoming data into an analog signal that is conveyed to the user's telephone.

[0010] The present invention provides the system with additional capability in

Docket: D2647

a manner that permits the cost to be distributed over a broad client base with minimal expense. When a telephone receiver goes off-hook, the Media Telephony Adapter (MTA) notifies the Call Agent, which instructs the MTA to provide a dial tone and requests digits. In the illustrated embodiment, this request is communicated via NetworkCentricSystem Protocol, which is a variant of the Media Gateway Control Protocol (MGCP). The MTA then creates a pass-through connection from the user to a Dial Server, which contains the processing hardware and software to further analyze the incoming audio signal. If the Dial Server detects dual-tone multifrequency tones (DTMF), then it collects those digits and forwards them to the MTA. The MTA then sends this information to the CA, which attends to the completion of the call over a network connection using VoIP.

[0011] Since the centralized Dial Server can be provided with considerably more processing power than could economically be located in the MTA, it can be also be given such voice analyzing capabilities as are needed to permit it to interpret the spoken name of a party, and then look it up in a data base to determine that party's telephone number. The Dial Server then reports the digits of the telephone number to the MTA, which then passes this information to the CA for completion of the call.

[0012] In addition to permitting the use of voice dialing, the flexibility of this system permits other applications as well. For example, by providing the data base associated with the DS with the appropriate information, the system can be set up to dynamically select a proper telephone number depending on the time of day or schedule of the called party. Both the CA and the Dial Server can be combined

Docket: D2647

into one device, where warranted. The use of protocols other than VoIP that are suitable for communicating over networks are within the scope of this invention.

Also, an interface can be provided to permit this system to synchronize with the data base of a personal digital assistant, company list, mail program, or other data base.

[0013] Because the necessary hardware and software is centrally located, these and other services can be provided to the subscriber at minimal additional cost.